

INSTALLING GROOVE

LOADING GROOVE

SELECTING SOUNDS

1. Connect your synthesizer to your computer with a USB cable.
2. Launch the Sound Librarian application.
3. Switch to the USER OSCILLATORS tab.
4. Drag and drop the **Groove** plugin file into any available slot.
5. Click the SEND ALL button in the USER OSC/FX group.

INSTALLING GROOVE

LOADING GROOVE

SELECTING SOUNDS

For KORG **prologue** and **minilogue xd**:

1. Start from an initialized patch.
2. In the MIXER, set VCO1 level to min and MULTI level to max.
3. In the MULTI ENGINE, set the switch to USR and then turn the TYPE dial to select **Groove**.

For KORG **NTS-1**:

1. Turn the device off and on to initialize the patch.
2. Press the OSC button.
3. Turn the TYPE dial to select **Groove**.

INSTALLING GROOVE

LOADING GROOVE

SELECTING SOUNDS

For KORG **prologue** and **minilogue xd**:

1. Press EDIT MODE and highlight PROGRAM EDIT.
2. Press function key #7 (**prologue**) or #10 (**minilogue xd**) repeatedly to access the plugin parameters, each of which corresponds to a different **Groove** keyboard zone.
3. Turn the PROGRAM/VALUE dial to pick a sound for the currently selected zone. Get started with odd sound numbers only (1, 3, 5...) and read about trigger probability in the user manual.

For KORG **NTS-1**:

1. Press and hold the OSC button.
2. Turn the TYPE dial to access the plugin parameters, each of which corresponds to a different **Groove** keyboard zone.
3. Turn the B knob to pick a sound for the currently selected zone. Get started with odd sound numbers only (1, 3, 5...). and read about trigger probability in the user manual.